

FT SERIES

Thermal Imaging Products



These FAX/POS series are mostly used for point-of-sale receipts at convenience stores, supermarkets, department stores, and retail stores. In addition, we offer lineups of this series in various grammages based on customer requests.

Grade name	Substance (gsm)	Caliper (μm)	Type		FSC CoC	Particularity				Sensitivity dynamic	Environmental Resistance	Image Life** Years	Application Particularity
			Non top	Top		BPA	No BPA Added	No BPS Added	No Phenol Added				
FT 190+	48	53	●			☑				●●○○	●○○○	5	Fax/POS
FT 100+	55	62	●			☑				●●○○	●○○○	5	Fax/POS
FT 210+	58	65	●		●	☑				●●●○	●○○○	5	Fax/POS
FT 220+	65	75	●		●	☑				●●●○	●○○○	5	Fax/POS
FT 390+	48	53	●				☑			●●○○	●○○○	7	Fax/POS
FD 210T	58	65	●		●		☑			●●●○	●○○○	7	Fax/POS
FT 320+	65	75	●		●		☑			●●●○	●○○○	7	Fax/POS
FT 330+	72	78	●		●		☑			●●●○	●○○○	7	Fax/POS
FT 510+	58	65	●		●		☑	☑	☑	●●●○	●○○○	10	Fax/POS
FT 520+	65	75	●		●		☑	☑	☑	●●●○	●○○○	10	Fax/POS

**The durability of the printed image according to our handling and storage standards.

- Our thermal paper should be stored at a constant temperature of 23 ± 5 °C and a relative humidity of 50 ± 10%. Exposure to strong sunlight or strong artificial light or the influence of aggressive chemicals should be avoided.

- Data represents product averages and does not constitute a warranty. Vender shall not be responsible for liability resulting from any deviation from this information. All products should be pretested to determine suitability for any specific purpose.

- For No BPS added, with less than 200 ppm.